



# Specification Table GE Cable Heads

Tool Code	From (Upper End)		To (Lower End)		Length	Tool Diameter	Pressure Rating	Temp. Rating	Weight	Voltage Rating
	Type	Diameter	Type	Diameter						
AS00003-1/4	CH	5/8" (15.88mm)	GO-PN	5/8" (15.88mm)	19.00 in (48.26cm)	0.63 in (1.6cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.63lbs. (0.28Kg)	452VDC
AS00003-7/32	CH		GO-PN	5/8" (15.88mm)	19.00 in (48.26cm)	0.63 in (1.6cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.63lbs. (0.28Kg)	452VDC
AS00003-9/32	CH	5/8" (15.88mm)	GO-PN	5/8" (15.88mm)	19.00 in (48.26cm)	0.63 in (1.6cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.63lbs. (0.28Kg)	452VDC
AS10006-3/8	CH	11/16" (17.46mm)	GO-PN	11/16" (17.46mm)	9.00 in (22.86cm)	0.69 in (1.75cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.88lbs. (0.397Kg)	452VDC
AS10006-5/16	CH	11/16" (17.46mm)	GO-PN	11/16" (17.46mm)	9.00 in (22.86cm)	0.69 in (1.75cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.88lbs. (0.397Kg)	452VDC
AS10006-7/32	CH	11/16" (17.46mm)	GO-PN	11/16" (17.46mm)	9.00 in (22.86cm)	0.69 in (1.75cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.88lbs. (0.397Kg)	452VDC
AS10006-9/32	CH	11/16" (17.46mm)	GO-PN	11/16" (17.46mm)	9.00 in (22.86cm)	0.69 in (1.75cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.88lbs. (0.397Kg)	452VDC
AS20004-1/4	CH	3/4" (19.05mm)	GO-PN	3/4" (19.05mm)	7.64 in (19.41cm)	0.75 in (1.91cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.81lbs. (0.37Kg)	1000VDC
AS20004-3/16	CH	3/4" (19.05mm)	GO-PN	3/4" (19.05mm)	7.64 in (19.41cm)	0.75 in (1.91cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.81lbs. (0.37Kg)	452VDC
AS20004-3/8	CH	3/4" (19.05mm)	GO-PN	3/4" (19.05mm)	7.64 in (19.41cm)	0.75 in (1.91cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.81lbs. (0.37Kg)	452VDC
AS20004-5/16	CH	3/4" (19.05mm)	GO-PN	3/4" (19.05mm)	7.64 in (19.41cm)	0.75 in (1.91cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.81lbs. (0.37Kg)	452VDC
AS20004-7/32	CH	3/4" (19.05mm)	SDX- PN	3/4" (19.05mm)	7.64 in (19.41cm)	0.75 in (1.91cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.81lbs. (0.37Kg)	452VDC
AS20004-9/32	CH	3/4" (19.05mm)	SDX- PN	3/4" (19.05mm)	7.64 in (19.41cm)	0.75 in (1.91cm)	21Kpsi (144.8MPa)	260°C (500°F)	0.81lbs. (0.37Kg)	452VDC
AS30003-5/16	CH	1" (25.4mm)	GO-PN	1" (25.4mm)	7.79 in (19.79cm)	1.00in. (2.54cm)	21Kpsi (144.8MPa)	260°C (500°F)	1.80lbs. (0.817Kg)	452VDC
AS30003-5/16M	CH	1" (25.4mm)	AES-PN	1" (25.4mm)	7.79 in (19.79cm)	1.00in. (2.54cm)	21Kpsi (144.8MPa)	260°C (500°F)	1.80lbs. (0.817Kg)	452VDC
AS30003-1/4	CH	1" (25.4mm)	GO-PN	1" (25.4mm)	7.79 in (19.79cm)	1.00in. (2.54cm)	21Kpsi (144.8MPa)	260°C (500°F)	1.80lbs. (0.817Kg)	452VDC
AS30003-1/8	CH	1" (25.4mm)	GO-PN	1" (25.4mm)	7.79 in (19.79cm)	1.00in. (2.54cm)	21Kpsi (144.8MPa)	260°C (500°F)	1.80lbs. (0.817Kg)	452VDC
AS30003-3/16	CH	1" (25.4mm)	GO-PN	1" (25.4mm)	7.79 in (19.79cm)	1.00in. (2.54cm)	21Kpsi (144.8MPa)	260°C (500°F)	1.80lbs. (0.817Kg)	452VDC
AS30003-3/8	CH	1" (25.4mm)	GO-PN	1" (25.4mm)	7.79 in (19.79cm)	1.00in. (2.54cm)	21Kpsi (144.8MPa)	260°C (500°F)	1.80lbs. (0.817Kg)	452VDC
AS30003-7/16	CH	1" (25.4mm)	GO-PN	1" (25.4mm)	7.79 in (19.79cm)	1.00in. (2.54cm)	21Kpsi (144.8MPa)	260°C (500°F)	1.80lbs. (0.817Kg)	452VDC
AS30003-7/32	CH	1" (25.4mm)	GO-PN	1" (25.4mm)	7.79 in (19.79cm)	1.00in. (2.54cm)	21Kpsi (144.8MPa)	260°C (500°F)	1.80lbs. (0.817Kg)	452VDC
AS30003-7/32BP	CH	1" (25.4mm)	GO-PN	1" (25.4mm)	7.79 in (19.79cm)	1.00in. (2.54cm)	21Kpsi (144.8MPa)	260°C (500°F)	1.80lbs. (0.817Kg)	452VDC
AS30003-9/32	CH	1" (25.4mm)	GO-PN	1" (25.4mm)	7.79 in (19.79cm)	1.00in. (2.54cm)	21Kpsi (144.8MPa)	260°C (500°F)	1.80lbs. (0.817Kg)	452VDC
AS30003HES	CH	1" (25.4mm)	GO-PN	1" (25.4mm)	7.79 in (19.79cm)	1.00in. (2.54cm)	21Kpsi (144.8MPa)	260°C (500°F)	1.80lbs. (0.817Kg)	452VDC







Tool Code	From (Upper End)		To (Lower End)		Length	Tool Diameter	Pressure Rating	Temp. Rating	Weight	Voltage Rating
	Type	Diameter	Type	Diameter						
AS60059A NIT	CH	1 11/16" (42.86mm)	GO-PN	1 11/16" (42.86mm)	13.03 in (33.10cm)	1.69 in (4.30cm)	21Kpsi (144.8MPa)	260°C (500°F)	5.57 lbs. (2.52Kg)	452VDC
AS60059A-NIT-M	CH	1 3/8" (42.86mm)	FN	1 3/8" (42.86mm)	13.03 in (33.10cm)	1.69 in (4.30cm)	21Kpsi (144.8MPa)	260°C (500°F)	5.57 lbs. (2.52Kg)	452VDC
AS60081-7/32	CH	1 11/16" (42.86mm)	SCH-PN	1 11/16" (42.86mm)	25.40 in. (64.52cm)	1.69 in (4.30cm)	21Kpsi (144.8MPa)	260°C (500°F)	6.81 lbs. (3.09Kg)	452VDC
AS60081-7/32SCH	CH	1 11/16" (42.86mm)	SCH-PN	1 11/16" (42.86mm)	25.40 in. (64.52cm)	1.69 in (4.30cm)	21Kpsi (144.8MPa)	260°C (500°F)	6.81 lbs. (3.09Kg)	452VDC
AS60081-9/32	CH	1 11/16" (42.86mm)	SCH-PN	1 11/16" (42.86mm)	25.40 in. (64.52cm)	1.69 in (4.30cm)	21Kpsi (144.8MPa)	260°C (500°F)	6.81 lbs. (3.09Kg)	452VDC
AS60081-5/16SCH	CH	1 11/16" (42.86mm)	SCH-PN	1 11/16" (42.86mm)	25.40 in. (64.52cm)	1.69 in (4.30cm)	21Kpsi (144.8MPa)	260°C (500°F)	6.81 lbs. (3.09Kg)	452VDC
AS60081HP-3/8	CH	1 11/16" (42.86mm)	HP-PN	1 11/16" (42.86mm)	25.40 in. (64.52cm)	1.69 in (4.30cm)	21Kpsi (144.8MPa)	260°C (500°F)	6.81 lbs. (3.09Kg)	452VDC
AS60081HP-7/16	CH	1 11/16" (42.86mm)	HP-PN	1 11/16" (42.86mm)	25.40 in. (64.52cm)	1.69 in (4.30cm)	30Kpsi (144.8MPa)	260°C (500°F)	6.81 lbs. (3.09Kg)	452VDC

[www.geoilandgas.com/wireline](http://www.geoilandgas.com/wireline)

GE Oil & Gas  
208 Ida Road  
Broussard, LA 70518  
United States

Tel: +1 337.837.2016