

## Caged Fullbore Flowmeter (6 arm CFBM)



The Caged Fullbore Flowmeter is run at the bottom of a production logging tool string. The spinner blades and cage assembly collapse down to tool diameter, enabling it to pass through tubing restrictions without damage.

### Description

The tool has a six arm, spring-loaded cage that centres the spinner in the middle of the flow and supports tool weight in deviated wells. A large diameter impeller measures flow rates with coverage over a large cross-section of the casing. The spinner runs on precision bearings and its rotation is sensed by zero drag Hall-effect detectors, and the signal from the sensors is converted into a flow rate measurement. The low mechanical threshold of the tool enables it to be used in low flow rates; normal output is 10 pulses per revolution with directional indication.

### Features

- High deviation and horizontal well logging
- Injection and production flow profiling
- Measurement of low flow rates
- Leak and cross-flow detection
- Interchangeable mechanical sections to match casing sizes from 4 1/2 to 9 5/8 in.
- Combinable with other Ultrawire\* PL Tools
- Connects to either a Spinner Electronics (CFBE) or a Capacitance/Temperature/Flow Tool (CTF)
- Modification kit available for connection to 1 3/8 in. CTF
- Lockable spinner for high rate injection wells (standard feature for 9 5/8 in. tools)
- Solid impeller shafts for very high rate wells. Baskets for casing sizes 3 in. to 9 5/8 in.

Specifications	
Temperature rating	350°F (177°C)
Pressure rating	15,000 psi (103.4 MPa)
Tool diameter	1 11/16 in. (43 mm)
Tool length	2.91 ft (0.889 m)
Tool weight (dependant on spinner and cage sizes)	10 lbs (4.5 kg) for 1 11/16 in. tool with 7 in. cage
Sensor measure point (from bottom of the tool)	13.5 in. (349 mm)
Output	10 pulses/rev (directional)
Spinner threshold	1.7 ft/min (0.01 m/s) (approx), 100 bpd in 7 in. casing
Max fluid velocity	500 ft/min (2.54 m/s), 28,250 bpd in 7 in. casing
Casing range	4 1/2 in. to 9 5/8 in.
Materials	Corrosion resistant throughout



GE imagination at work

Visit us online at:  
[www.ge-energy.com/wireline](http://www.ge-energy.com/wireline)

\*Trademark General Electric Company.  
Copyright ©2012 General Electric Company. All rights reserved.  
GEA18954B (01/2012)